

FASTEST RESPONSE

MULTI-TOUCH SCREEN

Support from Single up to Unlimited Touch Point



TOUCH SURFACE FEATURES

Available Sizes	27", 32", 40", 42", 46", 55", 60", 70", 80", 90", 103", 105"
Thickness	Touch Bezel Thickness (from glass to frame surface) 21.5" - 27": 4.7 mm 32" - 55": 4.9 mm Frame Thickness (with glass) 21.5" - 27": 6.9 mm 32" - 55": 8.8 mm
Wireless (Optional)	Multi-Touch over Air
Touch Points	True Multi-Touch (Detects 32+ (unlimited) touch points simultaneously) Plus: 32+ (unlimited) touch points Standard: 12 Touch Points Basic: 6 Touch Points Dual: 2 Touch Points
Touch Glass	• Ultra-Smooth Mighty Glass • Glass Thickness 21.5" - 27": 2 mm 32" - 46": 3 mm 55": 4 mm
Sample Rate	Up to 200 fps
Power Supply	21.5" - 46": USB Powered 55": 5V/4A power adapter
Interface	USB 2.0 (Full speed), compatible with USB 1.1 port, HID compliant, plug-and-play compatible USB A Type Receptacle
USB Extension	100 meters with Extender (Optional)
Waterproof (Optional)	IP64 Waterproof, Customizable to IP66 Waterproof (better than IP65 Waterproof)
Supported OS	Windows 8/7/Vista/XP, Mac OS X, Ubuntu/Fedora, Android

TOUCH CONTROLLER

Size	4.59" x 4.41" x 1.55"
Hard disk	m-SATA (SSD) 120GB
Network/Wireless	1*RJ45, 1*Wireless B/G/N
RAM	4GB
Operating System	Windows 7/8/32/64bits
CPU Type	Intel Core i3/i5/i7
North Bridge	2 x 204Pin
Memory Type Supported	DDR3 1333/1600
Max Memory Supported	16GB
Dual Channel Mem Supported	1 x Full size mini PCI Express with mSATA support
Other	1 x Half size mini PCI Express
Onboard Video	Intel HD Graphics 4000 Integrated by CPU
Channel	8 Channel
Max LAN Speed	10/100/1000Mbps
Interface	4 USB / 1 HDMI / 1 RJ45
HDMI (Mini)	1
Material	Chassis: Aluminum and Plastic



www.idisplay.co.th